

GT5000

“Presenting” the GT5000 Series TTW ATM

Genmega introduces the **GT5000** series ATM. A high performance yet economical **Through-The-Wall ATM** solution with the look and feel of a full bank ATM. Designed for wall or Kiosk installation, the **GT5000** series makes new TTW installation or replacements a snap. Built with the same compact modular components as your existing Genmega machines and engineered for easy installation and reliable operation. The **GT5000** includes high-end features like a 15” High Bright LCD which support custom advertisements and a 3-cassette cash dispenser with motorized cash presenter. A new Touch-Screen rear-service panel allows convenient and safe access for ATM Operators and Service personal.

The **GT5000** series ATM is ADA compliant and Chip Card (EMV) ready, including a PCI / Interac certified encrypting PIN pad (EPP), a voice guidance system, and lighted action indicators (including lighted keypad). Features of a high end **Through-The-Wall ATM** with the low maintenance and reliability that Genmega delivers makes this an excellent TTW solution.



www.genmega.com

GENMEGA

GT5000

Integrated Illuminated Topper Sign

High Visibility LED Sign
Attract Customers

LCD Screen

15 inch color TFT-LCD Panel
High bright LED backlight (800cd/m²)
1024 x 768 (XGA+) Resolution

Printer

80mm/3" Receipt Printer
200DPI monographic printing

PIN Entry Device

16-key alpha numeric keypad
PCI / Interac Certified
Triple-DES (TDES) EPP

Rear Service Panel

7 inch color touch screen
Backlit TFT LCD panel
800 x 480 Resolution

Communication

56Kb Internal Modem
TCPIP Ethernet - SSL



CPU

Cortex-A8 32-bit CPU
DDR2 256MB RAM / WinCE 6.0 OS
Electronic Journal > 40K transactions

ADA

Voice Guidance
Lighted Transaction Guidance
Accessible Keypad Layout

Card Reader

DIP Style Magnetic Card Reader
EMV - Optional

Security

UL291 Business Hours Vault
Electronic Lock or Cencon (optional)

Cash Dispenser

1 x 1700 Note Cassette
2 x 1700 Note Multi-Cassette
3 x 1700 Note Multi-Cassette
Presenter Module

Dimensions

Height = 56.7"
Width = 24.1"
Depth = 33.9"
Weight = 570 lbs

Operating Environment

Temperature range : 40°F - 95°F
Relative humidity : Non-condensing=15%-85%

Power Requirements

110/220 VAC ± 10%, 50/60 Hz, 145 Watts

