

# Monimax™ 7600D

Value, Delivered

*Multi-functional ATM that maximizes operation efficiency.*

## Features

- **Powerful Financial-Transaction** - With Microsoft® Windows® XP platform and Intel® Pentium® processor, faster and larger transaction is guaranteed. Also standardized design allows multi vendor solutions.
- **High Scalability** - Monimax 7600D is the multi-functional ATM supporting various additional financial services. Its open architecture allows for easy upgrades and expansion.
- **Reliability** - Monimax 7600D guarantees high reliability and safety by satisfying demanded standards for supporting financial transaction such as UL 291 level 1 and VISA certified encrypting PIN pad (Triple-DES).
- **Side Access Design for Easy Operations** - Monimax 7600D offers both side and rear access providing flexibility for drive-up installations and operational convenience.



Driving tomorrow's technology  
**NAUTILUS HYOSUNG**



### Dependable Customer Service:

We understand the importance of speedy resolution to any issues arising in the operation. Our representatives offer real solutions with real results for maximum return on your investment.



# MoniMAX™ 7600 D

Value, Delivered



## System Control

- Intel® Pentium® IV processor
- Microsoft® Windows® XP

## Communication

- TCP/IP(SSL configurable)

## Optional

- Dial-up, Wireless, X.25

## Application Software

- NDC+, DDC912, WEB enabled

## Customer Display

- 15" color TFT LCD

## Optional

- Privacy filter
- Sunlight readable

## Supervisor Operation

- 15" TFT color LCD, Touch screen

## Input Type

- 4x2 function keys
- **Optional** touch screen
- PCI compliant EPP
- DES, T-DES, RSA
- ADA compliant

## Card Handling

- Motor driven card reader

## Optional

- Dip type card reader
- EMV level 1, 2 compliant
- Anti-skimming

## Cash Dispensing

- 3,000 notes cassette (Up to 4 cassettes)
- Bundle retraction
- Automatic shutter

## Depository

- Envelope depository

## Optional

- Bulk check acceptor
- Bulk note acceptor

## Printers

- Graphical thermal receipt printer
- Electronic journal

## Optional

- Journal printer(Dot, Thermal)

## Security

- UL 291 level 1
- Dial lock

## Optional

- Electronic lock
- KABA Mas Cencil lock

## Miscellaneous

- Lead-through indicator
- Illuminated signage

## Optional

- Contactless card
- 1D/2D barcode reader

## Power Supply

- AC 110 ~ 240V, 50 ~ 60Hz
- Backup battery  
(Reserving last traction & safe shutdown)

## Operating Environment

- Temperature  
0°C ~ 40°C (32°F ~ 104°F)

## Optional

- -31°F ~ 122°F (-35°C ~ 50°C)
- Humidity  
20% ~ 80%

## Dimensions

- Height : 1,460mm (57.5")
- Width : 760mm (29.9")
- Depth : 1,050mm (41.3")
- Weight : 650kg (1,433 lbs)

Side access

Rear access

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.



**HYOSUNG**  
NAUTILUS HYOSUNG INC.

Cheongdam Bldg., 52 Cheongdam-Dong, Gangnam-Gu, Seoul, Korea 135-764  
TEL: +82-2-510-0441 FAX: +82-2-3442-7993  
<http://www.nautilus.hyosung.com>