Tranax 4000T

Through The Wall **Solution**

The all new **Tranax 4000T** ATM provides an economical, high performance through-the-wall solution. Designed and built with compact **modular** components and engineered for **easy installation**.

The 4000T offers a host of high-end features including a **10.4" High-Bright Color LCD** supporting custom screen advertisements and communication via **56K Modem** or integrated **Ethernet (SSL)**.

The Tranax 4000T is **TDES** and **ADA** compliant out of the box, including a **PCI/VISA/Interac certified encrypting PIN pad (EPP)**, a voice guidance system, and lighted action indicators.

TRANAX

Discover the Tranax Difference

Tranax 4000T

TRANAX
www.tranax.com

4000T

INTEGRATED ILLUMINATED TOPPER
Integrated illuminated topper
for creating high visibility
and attracting customers

HIGH-BRIGHT MONITOR
7 inch diagonal 32-bit color, backlit
TFT LCD panel
800 x 600 SVGA resolution

ADA
Accessible keypad layout
Voice guidance
Lighted action indicators

PRINTER
3 1/8" Thermal receipt printer.
Can print custom graphic

CARD READER
Manual insert (dip) magnetic card reader
EMV (optional)

KEYPAD
16-key alphanumeric keypad
VISA/Interac PCI certified
Triple DES (TDES) compliant
Encrypting PIN pad (EPP)

CPU
Intel XScale® 32-bit CPU
Windows® CE operating system

REAR SERVICE PANEL
Perform Operator Tasks and Diagnostics

COMMUNICATION
56K dial-up modem or Ethernet (TCP/IP)
On-board SSL Encryption

CASH DISPENSER
Sliding cash dispensing unit for easy service
- 1,000 note removable cassette

SECURITY
UL 291 Business Hour listed
Electronic lock
Cencon Lock (optional)

SPECIFICATIONS

Dimensions
33" H 24" W 17" D
Weight: 250 lbs
*optional dispensers will increase overall weight

Operating Environment:
Temperature range: 40°F-95°F
Relative humidity: Non-condensing - 15%-85%

Options and Upgrades:
High-bright topper

INSTALLATION

The Tranax 4000T comes with a steel pedestal which can be adjusted from 25" to 35". The pedestal carries the entire weight of the machine so you can install the 4000T in thin walls or facades.

Tranax® and the Tranax logo are trademarks of Tranax Technologies, Incorporated. © 2009 Tranax Technologies, Incorporated. Specifications subject to change without notice. Tranax endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions.